

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization International Bureau





(43) International Publication Date 30 October 2003 (30.10.2003)

PCT

(10) International Publication Number WO 03/089188 A1

(51) International Patent Classification7: B23Q 1/00, 3/12

(21) International Application Number: PCT/GB03/01677

(22) International Filing Date: 17 April 2003 (17.04.2003)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

0209072.8 0211617.6 20 April 2002 (20.04.2002) GB 21 May 2002 (21.05.2002) GB

(71) Applicant (for all designated States except US): REN-ISHAW PLC [GB/GB]; New Mills, Wotton-under-Edge, Gloucestershire GL12 8JR (GB).


(72) Inventors; and

(75) Inventors/Applicants (for US only): COLLINGWOOD, David [GB/GB]; 1 Lawns Park, North Woodchester, Stroud, Gloucestershire, GL5 5PP (GB). FERGUSON, Graham, Richard [GB/GB]; Montrose, Coronation Road, Rodborugh, Stroud, Gloucestershire GL5 3SD (GB). HAYTER, Timothy, Donald [GB/GB]; 88 Parklands, Wotton-under-Edge, Gloucestershire GL12 7NR (GB). PRESTIDGE, Tim [GB/GB]; Kirkness House, 11 Edward Street, Bath, Somerset BA2 4DU (GB). RENTON, Clive, Esmond, Harwood [GB/GB]; Green Cottage, Sopworth Road, Luckington, Chippenham, Wiltshire SN14 6PA (GB). STOTT, Edward [GB/GB]; Armadale Cottage, Bailey Lane, Hewelsfield, Lydney, Gloucestershire GL15 6XE (GB). THOMAS, David, Kenneth [GB/GB]; 1 Clare Walk, Thornbury, Bristol, South Gloucestershire BS35 1EN (GB).

- (74) Agents: FOWLER, Maria, Jayne et al.; Renishaw plc, Patent Department, New Mills, Wotton-under-Edge, Gloucestershire, GL12 8JR (GB).
- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,

[Continued on next page]

(54) Title: MACHINE ADAPTATION



(57) Abstract: The invention relates to the transmission of power and/or data from/to a stationary part of a machine tool (200) to/from an accessory (100) mounted in the spindle (210) of the machine tool (200). A first electrical link or interface la,lb,lc,ld provides electrical communication between the stationary part (200) and the spindle (210), and a second electrical link or interface (3) is provided electrically connected to the first electrical link at the accessory mounting area (230). The second link (3) is in the form of electrical contacts. The invention extends to an accessory shank (360) for mounting to the spindle (210) of the machine tool, and also to an accessory (100) e.g. in the form of a measurement probe, connected to the said shank (360).